

**Seznam tarifnih oznak, za katere bodo avtonomne tarifne opustitve predvidoma nehale  
veljati s 31.12.2012**

	TARIC	Description	Rate of autonomous duty	Intended course of action
ex 2914 30 00	20	Stearoyl benzoyl methane (CAS RN 58446-52-9)	0 %	<b>DELETED</b>  As of 1/7/2012
ex 2930 90 99	69	2-Amino-4-methylsulphonyl- <i>N</i> -methylaniline (CAS RN 73097-51-5)	0 %	<b>DELETE</b>
ex 2930 90 99	82	Sodium toluene-4-sulphinate (CAS RN 824-79-3)	0 %	<b>DELETE</b>
ex 2934 99 90	78	1,2,4-Thiadiazole-3-acetic acid 5-[(ethoxycarbonyl)amino]-methyl ester (CAS RN 150215-07-9)	0 %	<b>DELETE</b>
ex 3208 90 91	10	Preparation on the basis of polyhydroxyamide containing at least naphthoquinone ester derivate or tosylate dissolved in $\gamma$ -butyrolactone and/or 2-methoxy-1-methylethyl acetate	0 %	<b>DELETE</b>
ex 3808 93 27	20	Organic solution of Clethodim (ISO), with a Clethodim content of 37 % ( $\pm$ 2 %) or 70 % ( $\pm$ 2 %) by weight	0 %	<b>DELETE</b>
ex 3815 19 90	41	Catalysts in the form of tablets, consisting of 60 % ( $\pm$ 2 %) by weight of copper oxide on a support of aluminium oxide	0 %	<b>NEW FOR DELETION</b>
ex 3824 90 97	47	4-Methoxysalicylaldehyde, dissolved in <i>N</i> -methyl pyrrolidone	0 %	<b>DELETE</b>
ex 3824 90 97	78	Mixture of phytosterols derived from wood and wood based oils (tall oil), in the form of powder with a particle size not more than 300 $\mu$ m, containing by weight: — 60 % or more, but not more than 80 % of sitosterols, — not more than 15 % of campesterols, — not more than 5 % of stigmasterols, — not more than 15 % of betasitostanols	0 %	<b>NEW FOR DELETION</b>
ex 3919 90 00	55	Rolls of biaxially oriented polypropylene film with: — a self adhesive coating, — a width of 363 mm or more, but not more than 507 mm, — a total film thickness of 10 $\mu$ m or more but not more than 100 $\mu$ m, for use in the protection of LCD displays during the manufacturing of LCD modules(1)	0 %	<b>DELETE</b>
ex 7005 10 25	10	Float glass: — of a thickness of 2,0 mm or more but not more than 2,4 mm, — coated on one surface with a fluorine doped tin dioxide reflective layer	0 %	<b>DELETE</b>

**Seznam tarifnih oznak, za katere bodo avtonomne tarifne opustitve predvidoma nehale  
veljati s 31.12.2012**

	TARIC	Description	Rate of autonomous duty	Intended course of action
ex 7006 00 90 ex 8529 90 92	60 46	Soda-lime glass plates with: — a strain point of more than 570 °C — a thickness of 1,7 mm or more but not more than 2,9 mm — dimensions of 1144 mm (±0,5 mm) × 670 mm (±0,5 mm) or 1164 mm (±0,5 mm) × 649 mm (±0,5 mm) and — whether or not containing: — an indium-tin oxide film, or — a grid of electrodes made from silver paste covered by dielectric material	0 %	DELETE  DELETE
ex 7007 19 20	20	Tempered or semi-tempered glass plate of a diagonal size of 81 cm or more, but not more than 186 cm, with one or more polymer layers, whether or not painted or with coloured or black ceramics around the surrounding edges, for use in the manufacture of goods falling within heading 8528(1)	0 %	DELETE
ex 8407 31 00	10	Two stroke internal combustion engines, of a cylinder capacity of not more than 30 cm <sup>3</sup> for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00(1)	0 %	DELETE
ex 8419 89 98	30	Apparatus for vapour deposition of parylene for use in the manufacture of drug eluting stents(1)	0 %	DELETE
ex 8419 89 98	40	Solution preparation apparatus for the treatment of materials by a process involving a change of temperature for use in the manufacture of drug-eluting stents(1)	0 %	DELETE
ex 8462 21 80	10	Numerically controlled stent crimping machine comprising a base, a pneumatic crimp head and a motorised product positioning mechanism (V-block) to crimp a stent onto the balloon of a catheter using radial pressure in the manufacture of drug eluting stents(1)	0 %	DELETE
ex 8477 59 80	10	Machinery for working rubber or plastic for use in the manufacture of drug-eluting stents(1)	0 %	DELETE
ex 8529 90 65	80	Scan driver boards for generating electric pulses for scanning to certain electrodes in a glass panel, comprising at least semiconductor chips	0 %	DELETE
ex 8540 91 00	95	Slit or slot mask ("shadow mask"), excluding masks with continuously vertical slits, with a diagonal measurement of 697,5 mm or more, but not more than 782,9 mm	0 %	NEW FOR DELETION