

List of "Suspensions & Quotas"

Round 1-7-2013

November, 2012

DISCLAIMER: The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the paper editions of the Official Journal of the European Union is deemed authentic.

CN code	Description	Q/S
2922 41 00	L-Lysine monohydrochloride whether or not in a water solution (CAS RN 657-27-2 / CAS RN 56-87-1)	Q/t,
3105 40 00	MAP - Monoammonium phosphate (CAS RN 7722-76-1)	Q/kg,
3824 90 97	Mixture of tertiary amines containing by weight: — 66,5 % to 76 % of dodecyldimethylamine — 21 % to 30 % of dimethyl(tetradecyl)amine — less than 1,5 % of decyldimethylamine — more than 1 % of hexadecyldimethylamine for use in the production of amine oxides (1)	Q/t,
7801 10 00	Primary Lead ingot 99,99 % (CAS RN 7439-92-1)	Q/t,
ex 8504 40 82	Electric rectifier, with a capacity of not more than 1 kVA, for use in the manufacture of hair removal apparatus (1)	Q/4500000p/st,
ex 8526 91 20	Assembly for GPS system having a position determination function	Q/3000000p/st,
1104 29 17	Non-food "natural resin" obtained from sorghum grains possessing the following characteristics: - a dry weight of no less than 26.4 kg (i.e., 58 pounds) per bushel; - a moisture content at harvest of no more than 14 %; and - an anti-oxidant level higher than 150 parts per million used in the manufacture of loose-fill packaging products	S
2007 50 60 2007 99 50	Pink guava puree concentrate: — not frozen, — of the Genus <i>Psidium armeniaca</i> L., — with a Brix value of 19 or more but not more than 20, — with an acidity of 0,5 % or more but not more than 1,5 % expressed as citric acid	S
2007 50 90 2007 99 39 2007 99 50	Apricot puree: — concentrate, — of the Genus <i>Prunus armeniaca</i> L., — with a Brix value of 30 or more but not more than 33, — with an acidity of 2,0 % or more but not more than 3,6 % expressed as citric acid	S
2007 99 31 2007 99 50	Acerola purée concentrate: — Frozen, — Of the Genus <i>Malpighia punicifolia</i> L., — with a Brix value of 20 (\pm 3), — with an acidity of 2,5 % or more but not more than 4,5 %	S

CN code	Description	Q/S
2007 99 31 2007 99 39	Peach purée concentrate : – Not frozen, – Of a Genus <i>Prunus persica</i> L., – With a Brix value of 29 or more but not more than 33, – With an acidity of 0,8 % or more but not more than 2,2 %	S
2007 99 31 2007 99 50	Apricot purée concentrate: – not frozen, – of the Genus <i>Prunus armeniaca</i> L., – with a Brix value of 28 or more but not more than 33, – with an acidity of 2.5 % or more but not more than 5.5 %	S
2007 99 31 2007 99 39 2007 99 50	Apple purée concentrate: – non-frozen, – of the Genus <i>Malus x domestica</i> (Borkh fruit), – with a Brix value of 29 (\pm 2), – with an Acidity of 0.5 or more but not more than 0.7 %	S
2007 99 39 2007 99 50	Peach puree concentrate: – not frozen, – of the Genus <i>Prunus persica</i> L., – with a Brix value of 30 or more but more than 33, – with an acidity of 0,8 % or more but not more than 1,5 %, expressed as citric acid	S
2007 99 39 2007 99 50	Banana puree concentrate: – not frozen, – of the Genus <i>Musa</i> , – with a Brix value of 40 or more but not more than 42, – with an acidity of 0,4 or more but not more than 1,0 %, expressed as citric acid.	S
2007 99 50	Mango totapuri puree concentrate: – aseptic, – of the Genus <i>Mangifera</i> ("Totapuri"), – with a Brix value of 28 or more but not more than 30, – with an acidity of 0,60 % or more but not more than 1,10 %, expressed as citric acid	S
2007 99 50	Acidified banana puree: – Aseptic, – Of the Genus <i>Musa</i> ("Cavendish"), – With a Brix value of 21 or more but not more than 25	S
2007 99 50	Mango puree concentrate: – not frozen, – aseptic, – of the Genus <i>Mangifera indica</i> L, – with a Brix value of 26 or more but not more than 32, – with an acidity content of 0,3 % or more bur not more than 1,3 %, expressed as citric acid	S
2007 99 50	Guava puréeconcentrate: – Not frozen, – Of the Genus <i>Psidium guajava</i> L., – With a Brix value of 20 (\pm 3), – With an acidity of 0,8 % or more but not more than 1.5 %	S

CN code	Description	Q/S
2007 99 50	Red Papaya puree concentrate: — aseptic, — of the Genus Carica ("Red"), — with a Brix value of 24 or more but not more than 26, — with an acidity of 0,8 % or more but not more than 1,40 %, expressed as citric acid.	S
2007 99 50 2008 99 00	Banana puree: — aseptic, — of the Genus Musa, — with a Brix value of 21,0 or more but more than 25,0, — with an acidity of 0,30 % or more but not more than 0,60 %, expressed as citric acid, — with a pH of 4,6 or more but not more than 5,0.	S
2007 99 50	Mango puree concentrate: — not frozen, — of the Genus Mangifera, — with a Brix value of 28 or more but not more than 30, — with an acidity of 0,5 or more but not more than 1,3 %, expressed as citric acid	S
2007 99 50	Mango puree concentrate: — not frozen, — of the Genus Mangifera Indica L., — with a Brix value of 27g/100g or more but not more than 31g/100g, — with an acidity of 0,5 g/100g or more but not more than 1,2 g/100g, expressed as citric acid.	S
2007 99 50	Mango puree concentrate: — of the Genus Magnifera Indica L., — with a Brix value of 27 or more but not more than 32, — with an acidity content of 0,4 % or more but not more than 1,0 %, expressed as citric acid.	S
2007 99 50	Mangopurée: — Aseptic, — Concentrated, — Of the Genus Mangifera indica L, — With a Brix value of 28 or more but not more than 31.99	S
2007 99 50 2009 89 97	Mango puree: — aseptic, — of the Genus Mangifera, — with a Brix value of 16,2 or more but not more than 20,2, — with a pH of 3,6 or more but not more than 4,2, — with an acidity of 0,40 % or more but not more than 0,90 % expressed as citric acid	S
2007 99 50 2008 99 39	Apricot purée: — Aseptic, — Concentrated, — Of the Genus Prunus armenica L, — With a Brix value of 28 or more but not more than 31.99	S
2007 99 50 2007 99 93 2008 99 99	Mango puree concentrate: — of the Genus Mangifera indica L. ("Alphonso"), — with a Brix value of 18.5 (+/- 1.5), — with a pH of 3,8 (+/- 0,2), — with an acidity of 0,65 % (+/- 0,15), expressed as citric acid	S

CN code	Description	Q/S
2007 99 50	Mango puree concentrate: — aseptic, — of the Genus Mangifera ("Tommy Atkins"), — with a Brix value of 28 or more but not more than 30, — with an acidity of 0,4 % or more but not more than 1,4 %, expressed as citric acid.	S
2007 99 97	Red Guava pulp: — aseptic, — of the Genus Psidium ("Red"), — with a Brix value of 8 or more but not more than 10, — with an acidity content of 0,25 % or more but not more than 0,70 %, expressed as citric acid	S
ex 2008 60 19 ex 2008 60 39	Sweet cherries containing added spirit, whether or not with a sugar content of 9 % by weight, of a diameter of not more than 19,9 mm, with stone, for use in chocolate products (1)	S
2009 89 99	fruit juices, non-fermented, with no added alcohol, independent if they contain sugar or sugar substitutes or not, juice from other fruit or vegetable, with brix lower than 67	S
ex 2805 30 90	Rare earth metals, scandium and yttrium of a purity by weight of 98,5 % or more	S
2811 19 80	Phosphorous acid (CAS RN 10294-56-1)	S
2823 00 00	Titanium dioxide (CAS RN 13463-67-7) — with a purity by weight of 99 % or more and — a median value of the particle size of not less than 0,5 µm	S
ex 2823 00 00	Titanium dioxide (CAS RN 13463-67-7) with a purity by weight of 99,7 % or more and containing by weight: — not more than 0,005 % of potassium and sodium combined (expressed as elemental sodium and elemental potassium), — not more than 0,01 % of phosphorus (expressed as elemental phosphorus), for use in the metallurgy (1)	S
2903 39 90	2,3,3,3-Tetrafluoropropene (CAS RN 754-12-1)	S
2903 89 90	Chlorocyclopentane (CAS RN 930-28-9)	S
2905 39 95	décane-1,10-diol	S
2906 29 00	2-Phenylethanol (CAS RN 60-12-8)	S
2907 23 00	4,4'-isopropylidenediphenol (CAS RN 80-05-7)	S
2907 29 00	Biphenyl-2,2'-diol (CAS RN 1806-29-7)	S
2912 29 00	Isobutyl benzaldehyde (CAS RN 40150-98-9)	S
2914 50 00	3,4-dihydroxybenzophenone (CAS RN 10425-11-3)	S
2914 70 00	2,4'-Difluorobenzophenone (CAS RN 342-25-6)	S
2915 19 70	3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5)	S
2915 39 00	Isopentyl acetate (CAS RN 123-92-2)	S
2915 60 19	Ethyl butyrate (CAS RN 105-54-4)	S
2916 12 00	Ethyl Acrylate with purity of 99,5 % (CAS RN 140-88-5)	S
2916 12 00	2-(2-vinyloxyethoxy) ethyl acrylate (CAS RN 86273-46-3)	S
ex 2916 19 95	Potassium (E,E)-hexa-2,4-dienoate (CAS RN 24634-61-5)	S

CN code	Description	Q/S
2917 13 90	Dimethyl sebacate (CAS RN 106-79-6)	S
ex 2917 39 95	Bis(2-ethylhexyl)-1,4-benzenedicarboxylate (CAS RN 6422-86-2)	S
2918 29 00	Propyl-3,4,5-trihydroxybenzoate (CAS RN 121-79-9)	S
2918 30 00	Ethyl acetoacetate (CAS RN 141-97-9)	S
2918 99 90	Ethyl 2,3-epoxy-3-phenylbutyrate (CAS RN 77-83-8)	S
2919 90 00	Mono and distearyl acid phosphate (CAS RN 39471-52-8)	S
2920 90 10	2,4-Di-tert-butyl-5-nitrophenyl methyl carbonate (CAS RN 873055-55-1)	S
2920 90 85	Diphenyl octyl phosphite (CAS RN 15647-08-2)	S
2921 30 99	Cyclopropylamine (CAS RN 765-30-0)	S
2922 19 85	2-(2-Methoxyphenoxy)ethanamine hydrochloride (CAS RN 64464-07-9)	S
2924 29 98	Salicylamide (INN) (CAS RN 65-45-2)	S
2929 10 00	Butyl Isocyanate (CAS RN 111-36-4)	S
2931 00 99	(Z)-prop-1-en-1-ylphosphonic acid (CAS RN 25383-06-6)	S
2932 99 00	1-(2,2-Difluorobenzo[d][1,3]dioxol-5-yl)cyclopropanecarboxylic acid (CAS RN 862574-88-7)	S
2933 19 90	Allyl-5-amino-4-(2-methylphenyl)-3-oxo-2,3-dihydro-1H-1-pyrazolcarbothioate (CAS RN 473799-16-5)	S
2933 29 90	Imazalil (ISO) (CAS RN 35554-44-0)	S
2933 39 99	Tert-butyl 3-(6-amino-3-methylpyridin-2-yl)benzoate (CAS RN 1083057-14-0)	S
2933 49 90	Ethyl 4-oxo-1,4-dihydroquinoline-3-carboxylate (CAS RN 52980-28-6)	S
2933 99 80	Paclobutrazol (ISO) (CAS RN 76738-62-0)	S
2933 99 80	2,3-Dihydro-1H-pyrrol[3,2,1-ij]chinolin (CAS RN 5840-01-7)	S
2934 99 90	4-Isopropylmorpholine (CAS RN 1004-14-4)	S
2934 99 90	Indoxacarb (CAS RN 173584-44-6) — with or without its isomer — fixed or not on a support of silicon dioxide	S
2938 90 90	Steviol Glycosides with a purity of 95 % or more [in the form of granules, comprimates or powder] for use in the manufacture of products of food and drink industry	S
3204 11 00	Dye preparation, nonionic, containing the azo dyes Blue REG6080 and Red RA 10463	S
ex 3204 11 00	Dye C.I. Disperse Yellow 54 also known as C.I. Solvent Yellow 114	S
ex 3204 11 00	Dye C.I. Disperse Yellow 241	S
3204 12 00	Preparation of acid dyes, anionic, containing the dyestuff anthrachinon Blue 14 52 200	S
3204 12 00	Dye preparation, anionic, containing mainly the azo dye RED GS3848	S
3204 13 00	Colour index basic violet 1 (CAS RN 603-47-4)	S

CN code	Description	Q/S
3204 13 00	Colour index basic blue 7 (CAS RN 2390-60-5)	S
3204 17 00	Dye C.I. Pigment Orange 5 (CAS RN 3468-63-1)	S
ex 3204 19 00	Dye C.I. Solvent Yellow 93	S
ex 3204 19 00	Dye C.I. Solvent Blue 104	S
3207 40 85	Glass flakes in the form of a powder of a thickness of 0.3 or more but not more than 10 microns coated with titanium dioxide or iron oxide	S
3212 19 90	Ink, consisting of a dispersion of silver and silver chloride in methyl propyl ketone, containing a polyester polymer, with a solid content by weight of 55 % or more, but not more than 57 %, and with a specific gravity of 1,40 g/cm ² or more, but not more than 1,60 g/cm ² , for use in the production of electrodes (1)	S
3707 90 20	Dry ink, under powder form, constituted of : — styrene acrylate copolymer, — amorphous silica, — polyolefin and — either black carbon, either organic pigment, to be used as revelatory in the manufacturing of faxes bottles or cartridges, printers or copiers (1)	S
3808 93 90	Tablet preparation containing : — at least 1,8 % and no more than 2,2 % of 1-methylcyclopropene (1-MCP) with a minimum purity of 96 % and — less than 0.05 % of each of the two impurities, 1-chloro-2-methylpropene et 3-chloro-2-methylpropene, of a kind used in post-harvest plant growth regulator for fruits, vegetables and ornamentals	S
3812 30 80	UV stabilizer; 1,6-Hexanediamine, N,N'-Bis(2,2,6,6-tetramethyl-4-piperidiny)-, polymers with morpholine-2,4,6-trichloro-1,3,5-triazine reaction products, methylated (CAS RN 193098-40-7)	S
3812 30 80	UV stabilizers, consisting of — a hindered amine light stabilizer (1,6-Hexanediamine, N,N'-Bis(2,2,6,6-tetramethyl-4-piperidiny)-, polymers with morpholine-2,4,6-trichloro-1,3,5-triazine reaction products, methylated (CAS RN 193098-40-7)) — with heterocyclic and/or chemically modified phenolic compounds, — for use as a light stabilizer in agricultural plastic films	S
3824 90 97	Platinum oxide (CAS RN 12035-82-4) fixed on a porous support of aluminium oxide (CAS RN 1344-28-1), containing — by weight 0,1 % or more but not more than 1 % of platinum, and — 0,5 % or more but not more than 5 % of ethylaluminium dichloride (CAS RN 563-43-9)	S
3824 90 97	Diethylene glycol propylene glycol triethanolamine titanate complex[es] (CAS RN 68784-48-5)	S
3824 90 97	Preparation of C, C'-azodi (formamide), magnesium oxide and zinc bis (p-toluene sulfinate) in which the gas formation from C, C'-azodi (formamide) occurs at 135° C	S

CN code	Description	Q/S
3824 90 97	[Tytan TET] titanium chelate of triethanolamine and isopropyl alcohol complexes(CAS RN 36673-16-2)	S
ex 3824 90 97	Mixture of divinylbenzene-isomers and ethylvinylbenzene-isomers, containing by weight 56 % or more but not more than 80 % of divinylbenzene	S
3901 20 90	High Density Polyethylene additive free, in powder form	S
3905 30 00	Viscous preparation, essentially consisting of Poly(vinylalcohol), an organic solvent and water [for use as protective coating of wafers during the cutting process] (CAS RN 0019860-7 / CAS RN #?) (1)	S
3905 91 00	Water-soluble ethylene vinyl alcohol copolymer, containig by weight not more than 18 % of ethylene (CAS RN 026221-27-2)	S
3905 99 90	Poly(butyrat of vinyl) (CAS RN : 63148-65-2): — containing hydroxyl groups of 17.5-20 mol % and — with a median particle size (D50) greater than 0.6 mm	S
3906 90 90	Polyacrylate, polymerized from stearyl methacrylate, isooctyl acrylate and acrylic acid, dissolved in isopropyl palmitate	S
3906 90 90	Aromatic polyurethane hexaacrylate which does not contain organotin compounds, dissolved in trimehylolpropane triacrylate	S
3907 20 20	Polytetramethylene ether glycol with a molecular weight of more than 2000 (CAS RN 25190-06-1)	S
ex 3911 90 99	Poly(ethyleneimine)	S
3919 10 80 3919 90 00	Rolls of polyester, urethane or polycarbonate foil: — with pressure sensitive silicone polymer adhesive — of a total thickness of not more than 0,50 mm, — of a total width of 10 mm or more, but not more than 100 cm, of a kind used for the protection of the surface of products of headings 8521 and 8528	S
3919 90 00 3921 90 60	Printed laminated sheet — with a core layer of glass fabric — with two layers of poly(vinylchloride) — on one side covered with a layer of poly(vinylfluoride) — whether or not with a pressure sensitive adhesive layer on the other side — whether or not with a release film — with a toxicity as determined by test method ABD 0031 of not more than 50 ppm hydrogen fluoride, not more than 85 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together — with a flammability within 60 seconds of not more than 110 mm as determined by test method FAR 25 App.F Pt. I Amdt.83 — with a weight (without release film) of 490 (± 45) g/m ² without adhesive layer or of 580 (± 50) gm ² with pressure sensitive layer	S

CN code	Description	Q/S
3919 90 00 3920 99 59	<p>Printed laminated sheet with a central layer of poly(vinylchloride), coated on both sides with a layer of poly(vinylfluoride)</p> <ul style="list-style-type: none"> — whether or not with a pressure or heat sensitive adhesive layer — whether or not with a release film — with a toxicity as determined by test method ABD 0031 of not more than 70 ppm hydrogen fluoride, not more than 120 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together — with a flammability within 60 seconds of not more than 130 mm as determined by test method FAR 25 App.F Pt. I Amdt.83 — with a weight (without release film) of 240 (± 30) g/m² without adhesive layer, of 340 (± 40) g/m² with heat sensitive adhesive layer or of 330 (± 40) gm² with pressure sensitive layer 	S
3919 90 00	<p>Self-adhesive film composed of:</p> <ul style="list-style-type: none"> — a top layer containing a mixture of emulsion polymers and titanium dioxide — whether or not containing a second layer of a mixture of vinyl acetate copolymer emulsions — not more than 6 % by weight of other additives — a pressure sensitive adhesive; and — covered on one side with a release liner <p>of a thickness of not more than 300 micron, whether or not with a separate self- adhesive over laminate protective film</p>	S
3919 90 00	<p>Self-adhesive film composed of</p> <ul style="list-style-type: none"> — a layer containing a mixture of thermoplastic polymer and additives — a layer containing a maleic anhydride copolymer — a layer containing a mixture of polyethylenes and additives — a layer containing a mixture of polyethylenes, additives and colour pigment — a pressure sensitive adhesive; and — covered on one side with a release liner <p>of a thickness of not more than 300 micron, whether or not with a separate self- adhesive over laminate protective film</p>	S
3919 90 00	<p>Film, with a thickness of 40µm or more, consisting of one or more layers of transparent polyester film :</p> <ul style="list-style-type: none"> — containing at least one infrared reflective layer with a total normal reflectance according to EN 12898 of 80 % or more — having on one side a layer with a normal emissivity according to EN 12898 of not more than 0,2 — coated on the other side with an pressure sensitive adhesive and a release liner 	S

CN code	Description	Q/S
3920 10 28 3920 10 89	Rolls of polyethylene foil: — not self-adhesive, — with acrylate polymer adhesive — of a total thickness of 0,025 mm or more, but not more than 0,7 mm, — of a total width of 60 mm or more, but not more than 66 cm, of a kind used for the protection of the surface of products of headings 8521 and 8528	S
3920 20 80	Polypropylene sheet having the following characteristics: — flame retardant level of UL 94 VTM-0 (0 .05 – 0.25 mm) and UL 94 V-0 (> 0.25 mm) — dielectric breakdown of a minimum of 13.1kV but not exceeding 60.0kV (as determined by test method ASTM D149) — tensile yield in a machine direction of a minimum of 4,400 psi but not exceeding 4,800psi (as determined by test method ASTM D882) — tensile yield in a transverse direction of a minimum 3,200psi but not exceeding 3,600psi (as determined by test method ASDM D882) — density range of a minimum of 0.988gm/cm ³ but not exceeding 1.035 gm/cm ³ (as determined by test method ASTM D792) — moisture absorption of a minimum of .01 % but not exceeding .06 % (as determined by test method ASTM D570) — comparative tracking index of 600 volts (as determined by test method ASTM D3638) Whether or not with a static decay time of less than 2 seconds and put up in rolls for use in the manufacture of insulators and isolators used in the electronics and electrical industries	S
ex 3920 62 19 ex 3920 62 19	Poly(ethylene terephthalate) film of a thickness of not more than 20 µm, coated on both sides with a gas barrier layer consisting of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm	S
ex 3920 92 00	Polyamide film of a thickness of not more than 20 µm, coated on both sides with a gas barrier layer which consists of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm	S
3920 99 28	Thermoplastic polyurethane film extruded, with: — a micro-rough surface, — an index of yellow lower than 2.5 and — light transmission higher to 87 % (for a molten thickness of 3.8mm), presented out of coils of a width going until 3m, and a thickness ranging between 0.38mm and 7.6 mm	S
3921 13 10	Rolls of open-cell polyurethane foam with a thickness of 2,29 mm (+/- 0,25 mm), surface-treated with a foraminous adhesion promoter and laminated to a polyester film and a layer of textile material	S
4104 49 19	Buffalo leather, splitted, chrome tanned synthetic retanned ("crust"), dry	S

CN code	Description	Q/S
4107 12 91	Bovine hide leather with thickness 1.1 mm – 1.7 mm, strength min. 8 MPa, flammability of not more than 80 mm/min, surface finished with colouring appointed for production of car seats and car interior body parts	S
5503 20 00	Hollow staple fibre, exclusively of two differently shrinking polyesters, with spiral formed crimp, coated with silicone	S
5510 12 00	Multi-ply yarns of viscose fibre: — with yarn numbers 16/2 NE or 16/4 NE, — raw white or dyed, — spinning from fibres with a thickness of 1,2 denier or more, but not more than 1,5 denier and a length of 38 mm or more, but not more than 51 mm	S
5603 93 90	Non-wovens of polyester man-made fibres weighing more than 70 g/m ² but not more than 150 g/m ² and with a constant thickness of the material of 80 µm or more, but not more than 110 µm	S
7009 10 00	Automatically controlled mirror-glass fittings for rear-view mirrors, having the ability to reflect variable intensities of ambient light, whether or not equipped with a heating element	S
7019 19 10	Yarns of 33 tex or multiples of 33 tex (± 10 %) obtained using continuous glass filaments, with fibres of a diameter of 6 µm (± 0,5 µm)	S
ex 7019 19 10	Yarn of 33 tex or a multiple of 33 tex (± 13 %) made from continuous spun-glass filaments with fibres of a diameter of 9 µm (- 1 µm / + 1,5 µm)	S
ex 7326 90 98 ex 8529 90 49 ex 8529 90 92	TV pedestal stand with metal upper part for fixation and stabilization of TV cabinet case/body	S
7505 12 00	Round Bars for high performance comply with the following standards : — AMS 5662 : Inconel 718 — AMS 5708 : Waspalloy — AMS 5772 : Haynes 188 — UNS N07080 : Alloy 80A (Nimonic 80A) of a kind used in the aerospace industry	S
7505 22 00	Coils of wires for high performance applications materials conforming with the following standards : — AMS 5662 : Inconel 718 — AMS 5708 : Waspalloy — AMS 5772 : Haynes 188 — UNS N07080 : Alloy 80A (Nimonic 80A) of a kind used in the aerospace industry	S
ex 7607 11 90	Laminated aluminium foil with: — 99 % or more of aluminium, — a silica and water glass free hydrophilic coating, — a total thickness of not more than 0,120 mm, — a tensile strength of 100 N/mm ² or more (as determined by test method ASTM E8), and — an elongation at break of 1 % or more	S

CN code	Description	Q/S
ex 7607 20 90	Lubricating entry sheet of a total thickness of not more than 350 µm, comprising of: — a layer of aluminium foil of a thickness of 70 µm or more but not more than 150 µm, — a water soluble lubricant of a thickness of 20 µm or more but not more than 200 µm and solid at room temperature, for use in the manufacture of printed circuit boards (1)	S
8102 94 00	Unwrought molybdenum, including bars and rods obtained simply by sintering, for use as an alloying element in smelting furnaces in the production of nickel and cobalt-based alloys and special stainless steels (1)	S
8102 95 00	Molybdenum and articles thereof, including waste and scrap: - - Bars and rods, other than those obtained simply by sintering, profiles, sheets, strip and foil, for use as an alloying element in smelting furnaces in the production of nickel and cobalt-based alloys and special stainless steels (1)	S
8102 96 00	Molybdenum and articles thereof, including waste and scrap: - - Wire for use as an alloying element in smelting furnaces in the production of nickel and cobalt-based alloys and special stainless steels (1)	S
8102 99 00	Molybdenum and articles thereof, including waste and scrap, specifically: -- forms other than unwrought molybdenum, molybdenum in bars (rods) or molybdenum wire, for use as an alloying element in smelting furnaces in the production of nickel and cobalt-based alloys and special stainless steels (1)	S
ex 8104 30 00	Magnesium powder: — of purity by weight of 98 % or more, — with a particle size of 0,2 mm or more but not more than 0,8 mm	S
8105 90 00	Bars made of Cobalt alloy containing : — 35 % Cobalt, — 25 % Nickel, — 19 % chromium and 7 % steel, conforming to the material standard AMS 5842 (usual name MP 159) of a kind used in the aerospace industry	S
ex 8305 20 00	Staples of a width of 12 mm (± 1 mm) and a depth of 8 mm (± 1 mm) for use in copiers and printers (1)	S
8501 10 99	Motor for electric fryer : — With a rotation speed between 3500 and 5000 rpm in load and of 6500 rpm vacuuous, — With a power supply voltage between 100V and 240V in DC power	S
8503 00 99	Fuel cell membrane, solely for fuel cells of heading 8503	S

CN code	Description	Q/S
ex 8504 40 82	<p>Printed circuit board equipped with a bridge rectifier circuit and other active and passive components</p> <ul style="list-style-type: none"> — with two output connectors — with two input connectors which are available and useable in parallel — able to switch between bright and dimmed operation mode — with an input voltage of 40V (+ 25 % -15 %) or 42 V (+ 25 % -15 %) in bright operation mode, with an input voltage of 30 V (± 4 V) in dimmed operation mode, or — with an input voltage of 230V (+20 % -15 %) in bright operation mode, with an input voltage of 160 V (± 15 %) in dimmed operation mode, or — with an input voltage of 120V (15 % -35 %) in bright operation mode, with an input voltage of 60 V (± 20 %) in dimmed operation mode — with an input current reaching 80 % of its nominal value within 20 ms — with an input frequency of 45 Hz or more, but not more than 65 Hz for 42V and 230V, and 45-70Hz for 120V versions — with a maximum inrush current overshoot of not more than 250 % of the input current — with a period of the inrush current overshoot of not more than 100ms — with an input current undershoot of not less than 50 % of the input current — with a period of the inrush current undershoot of not more than 20ms — with a presettable output current — with an output current reaching 90 % of its nominal pre-set value within 50 ms — with an output current reaching zero within 30 ms after removal of the input voltage — with an defined failure status in case of no-load or too-high load (end-of-life function) 	S
ex 8504 40 82	<p>Transformer in a housing with</p> <ul style="list-style-type: none"> — a rated power of not more than 30 W — an input voltage of 90 V or more, but not more than 305 V — an input frequency of 47 Hz or more, but not more than 63 Hz — a constant current output of 350 mA or more, but not more than 1.050 mA — an inrush current of not more than 10 A — an operating temperature range of -20 °C or more, but not more than +65 °C, suitable for driving LEDs 	S

CN code	Description	Q/S
8504 40 84	Transformer in a housing with — a rated power of not more than 30 W — an input voltage of 90 V or more, but not more than 305 V — an input frequency of 47 Hz or more, but not more than 63 Hz — a constant current output of 350 mA or more, but not more than 1.050 mA — an inrush current of not more than 10 A — an operating temperature range of -20 °C or more, but not more than +65 °C, suitable for driving LEDs	S
8505 11 00	Magnets made of an alloy of neodymium, iron and boron, or samarium cobalt, with an inorganic passivation (inorganic coating) with zinc phosphate (Zn ₃ (PO ₄) ₂), for the industrial manufacture of products in motor or sensory applications (1)	S
8507 60 00	Lithium-ion rechargeable batteries, with: — a length of 1477 mm or more, — a width of 1368 mm or more, — a height of 261 mm or more, — a weight of 320 kg or more, — a nominal capacity of 117 Ah or more but not more than 127 Ah, Put up in packs of 12 modules	S
8507 60 00	Rectangular modules for incorporation in lithium-ion rechargeable batteries: — Of a width of (W) : 352.5 mm (+/- 1mm) or 367,1 mm(+/- 1mm) — Of a depth of (D) : 300 mm (+/- 2mm) or 272,6 mm(+/- 1mm) — Of a height of (H) : 268,9 mm(+/- 1,4mm) or 229,5 mm (+/- 1mm) — Of a weight of : 45.9 kg or 46.3 kg — With a rating of : 75 Ah — Of a nominal voltage of : 60 V	S
8516 90 00	Inner pot of an electric fryer made with annealed aluminum : — With a coating resulting of a triple process: sanding, anodizing and a ceramic high-temperature coating > 200 °, — With an abrasion resistance refers to the test CF-HP A-VFN leaves n°07447	S
8522 90 49 8529 90 65	Electrical switch-board with a touch switch, with an electric conductor, with or without an integrated circuit, with or without an infra-red receiver for production of the products falling within headings 8521 and 8528	S
8522 90 80	Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and/or integrated circuits in products of heading 8521	S
8525 80 19	Camera module with a resolution of 1280*720P HD, with two microphones, for use in the manufacture of products of heading 8528	S

CN code	Description	Q/S
ex 8526 91 20 ex 8528 59 80	Integrated audio module (IAM) with a digital video output for connection to an LCD touch screen monitor, interfaced over the Media Oriented Systems Transport (MOST) network and transported over the MOST High protocol, with: <ul style="list-style-type: none"> — a printed circuit board (PCB) containing a Global Positioning System (GPS) receiver, a gyroscope, and a Traffic Message Channel (TMC) tuner, — a hard disk drive supporting multiple maps, — a HD radio, — a voice recognition system, — a connection to an external CD and DVD drive, — Bluetooth, MP3 and USB input connectivity, — a voltage of 10 V or more but not more than 16 V, for the use in the manufacture of vehicles in Chapter 87 (1)	S
8528 72 40	A main printed circuit board for an LCD television, comprising active and passive elements and incorporating a tuner	S
8529 90 65	Main printed circuit board for an LCD television, comprising active and passive elements not incorporating a tuner	S
8529 90 92	Painted aluminium parts with a thickness of 0,6 mm (+/- 0,1mm) for the front cover of television sets	S
8529 90 92	Ambient light LED diode board to be incorporated in goods of heading 8528	S
8529 90 92	Fastening and covering frame of rectangular shape made of aluminium alloy containing silicon and magnesium, with: <ul style="list-style-type: none"> — a length of 900 mm or more but not more than 1500 mm, — a width of 600 mm or more but not more than 950 mm, for use in the manufacture of TV sets (1)	S
8529 90 92	Mechanical device; which makes whole TV set or main body of TV set fixed to the TV stand with a metal or plastic underpinning part	S
8536 69 90	SCART type connectors, built into a plastic or metal housing, with 21 pins in 2 rows, for use in the manufacture of products falling within headings 8521 and 8528	S
ex 8536 90 85 ex 8538 90 99 ex 8543 90 00	Keypads, wholly of either silicone or polycarbonate, including printed keys with electrical contacting elements	S
8537 10 99	Electrical switch-board with a 5-way switch, with an electric conductor, with an integrated circuit, with or without an infra-red receiver for production of the products falling within headings 8521 and 8528	S
ex 8540 20 80	Photomultiplier consisting of a photocathode tube with 9 diodes or 10 diodes, for light of a wavelength of 160 nm or more but not more than 930 nm, of a diameter of not more than 14 mm and a height of not more than 94 mm	S
8544 42 90	PVC insulated flexible cable with: <ul style="list-style-type: none"> — a rated voltage of 250 V, — a rated current of 2 A or more, but not more than 8 A, — a nominal cross-section of wire(s) of 0,75 mm² (+/- 0,05 mm²) — connector(s) and/or plug(s) fitted at one or both ends, for use in the manufacture of products falling within headings 8521 and 8528	S

CN code	Description	Q/S
8703 10 18	Three or four wheeled electric motor driven vehicles (mobility scooters) having a maximum speed of 15 km/h and a maximum stopping distance of 4,5 m when travelling forwards on a horizontal surface and a continuous driving distance range of 35 km, fitted with a single seat, a separate adjustable steering column with a control unit, horn, and an electronic speed limiter, finger or thumb operated levers for acceleration, braking and reversing, a horizontal platform connecting the front and rear sections, and small wheels which are fixed and anti-tip at the rear	S
8708 50 35	Drive axle with differential, drop box gears, crown wheel and drive shaft for use in the manufacture of vehicles in Chapter 8427	S
8714 91 10	Bicycle frame, constructed from carbon fibres and artificial resin, painted, lacquered and/or polished	S
8714 91 30	Bicycle front fork, constructed from carbon fibres and artificial resin, painted, lacquered and/or polished	S
9001 90 00	Unmounted optical elements made from molded infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material	S
9002 90 00	Mounted lenses made from infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material	S
ex 9405 40 39	Electric light assembly containing: — printed circuit boards and — Light Emitting Diodes (LED) for the manufacture of backlight units for flat TV sets (1)	S

Legenda:

Q = kvota

S = opustitev